## DESCRIPTION OF PROPOSED WORKS

Underground concrete reservoir, dimensions 12 feet sby 20 feet site  State manner in which water is to be diverted, whether by dam or other works, whether through pipes, ditches, flumes, or other conduits. If water  110 feet shy 20 feet site water  110 feet shy 20 feet site site site shows a converse of the conduits. If water  110 feet shy 20 feet site site site shows a converse of the conduits. If water
uated on claim, water to be conveyed through six to three inch pip is to be stored in reservoirs it should be so stated and the location of the reservoir should be given with reference to the legal subdivisions.
approx. 50,000 feet North to property of Tonopah Shawmut Mines Co.
5. Estimated cost of works of reservoir and pipe line \$30,000.00
6. Estimated time required to construct works reservoir and pipe.
line Four (4) Months. 7. Remarks
For-use:of:applicant.
TONOPAH SHAWMUT MINES CO., LTD., , Applicant.
By Paul Erine Rink
Compared T. T. Jones. Mgr. Director.
This sheet inspected
PROTESTED by Catherine Dou <u>glass Hirsh, Febr</u> uary 2nd, 1920.
APPROVAL OF STATE ENGINEER
This is to certify that I have examined the foregoing appli
cation, and do hereby grant the same, subject to the following lim
itations and conditions:
ර යන සම්බන්ධයට සම්බන්ධයට සහ සම්බන්ධයට සිදුව සැම් කිරීම සිට්ට ජීවාදිය ජීවාදිය ජීවාදි ඉසිටම මෙසේ සහ
The amount of water to be appropriated shall be limited to th amount which can be applied to beneficial use, and not to excee
<u>nogs in S</u> cubic feet per second.
Actual construction work shall begin on or before
Proof of commencement of work shall be filed before
Work must be prosecuted with reasonable diligence and be complete
on or before the state of the s
Proof of completion of work shall be filed before
Application of water to beneficial use shall be made on or befor
Proof of the application of water to beneficia
use must be filed with State Engineer on or before
Thorawn by applicant WITNESS MY HAND AND SEAL this da
inch 9,1920